1263-1.6

"L.C." LOW CONSUMPTION FLUSH VALVE (1.6 GALS. PER FLUSH)

Polished chrome plated flush valve, diaphragm type, 1.6 gallons per flush, externally adjustable for water conservation, with 1" capped screwdriver angle stop with back-check, renewable main valve seat, equipped with push-button hydro-flush actuator through wall, wall plate for use with two gang gem box, wall flange, "Turn-to-Silence" equipment, with "Kwikfit" threaded union tailpiece, vacuum breaker, with 977 bedpan diverter valve, wall support, wall flange, spud nut and spud flange for 1½" top spud. Includes 194K Sweat Adaptor Kit.

Variations

- ☐ C – 3" Oscillating disc
- ☐ E – One wall bumper (for seat with cover or closed front seat without cover)
- ☐ F – Two wall bumpers (for open front seat without cover)
- ☐ L – Handle or push-button on front of valve
- ☐ T6 – Heavy cast wall flange with allen head set screw
- ☐ T7 – Nickel-silver handle, push-button, or oscillating disc, as applicable
- ☐ T8 – Sweat inlet stop
- ☐ T36 – Solid ring wall support for flush connection
- ☐ T42 – Sweat adapter kit for stop
- ☐ T46 – Split ring wall support for flush connection

Remarks

✻ *For use with 1.6 gallon low consumption water closet*



Delany Since 1879 Products™

P.O. Box 411 · Charlottesville · VA · 22902 • USA
Phone: (434) 296-0166 · Fax (434) 977-3596
Email: info@delanyproducts.com
Web: www.delanyproducts.com

©2009