

ULTRA Plus HYDRO-FLUSH CONCEALED

Description

Concealed rough brass flush valve hydraulically activated for 1.5" back entry wall hung or floor mounts water closets.

Flush Cycle

1.1 gpf / 4.2 Lpf High Efficiency

Specification

- Regulating screw for "True-in-the-Field" water conservation.
- Mashaeration self-cleaning bypass diaphragm.
- 1" wheel handled operated angle stop with back-check.
- Renewable main valve seat.
- ADA compliant hydro-flush actuator with pushbutton through the wall assembly. (or replaced by fixture manufacturer)
- 1.5" x 14.5" vacuum breaker with elbow flush connection for 1.5" back entry.
- SlipFit adjustable tailpiece.
- Sweat adapter kit.
- All rubber parts molded of chloramine resistant rubber.
- All exposed parts chrome plated.

Variations

- ☐ C - 3" Oscillating Disc
- ☐ GJ - Ground Joint Connection
- ☐ J - Screwdriver operated cotrol stop
- ☐ T48 - Valve for use with an access panel
- ☐ TS - TruStop 1" Angle Control Stop

Access Panels Supplied by Others

* Wall Size Required at time of Order. Size Range from 1" to 12"
Pricing will vary based upon size. *

Valve shall be in compliance to the applicable sections of ASSE 1037

