

PL1452-1

LOW CONSUMPTION URINAL FLUSH VALVE
(1 gpf / 3.8 Lpf per Flush)

Pulsar

Description

Battery powered, sensor activated, diaphragm operated, chrome plated exposed flush valve for 1-1/4" top spud urinals.

Flush Cycle

1 gpf/3.8 Lpf Low Consumption

Specification

- SmartChoice Technology software provides field adjustability for True-in-the-Field Water Conservation.
- 6 Volt DC non-latching solenoid valve.
- 6 Volt DC lithium battery (2CR5 type).
- Infrared sensor with Dual Infrared Transmitter Technology.
- Electronic range adjustment.
- Arming delay of 10 seconds prevents unintentional flushes.
- Electronic courtesy flush push button.
- Renewable main valve seat.
- 1" vandal resistant capped screwdriver angle stop with back-check.
- Sweat Adapter Kit
- Vacuum Breaker w/ 9" flush connection.
- Wall flange, spud nut and spud flange for 1-1/4" top spud.
- All rubber parts molded of Chloramine Resistant Rubber.

Variations

- GJ - Ground Joint Tailpiece
- SC - SlipFit Connection (adjustable joint tailpiece)
- G - Bumper on angle stop (for seat without cover)
- T6 - Wall flange with allen set screw.
- T36 - Solid ring wall support for flush connection
- T46 - Split ring wall support for flush connection
- TS - TruStop - Ball valve designed Control Stop
- VPS - Vandal Proof Control Stop with Key

