

TrueSense Plus Concealed

Description

In-wall sensor activated concealed Flushboy Ultra flush valve for concealed back spud wall hung or floor mount water closet.

Flush Cycle

1.6 gpf / 6 Lpf Low Consumption

Specification

- Regulating screw for "True-in-the-Field" water conservation.
- Mashaertor Self-Cleaning Bypass Diaphragm
- 9 volts DC low voltage transformer or battery.
- Renewable main valve seat.
- Infrared sensor with detector indicator light.
- Arming delay of ten (10) seconds prevents unintentional flushes.
- Six (6) second flush delay.
- One-Touch Flush electronic override push button.
- Latching solenoid valve (9 volt DC).
- Chrome plated die cast wall plates for sensor and flush valve with no visible fasteners (for 2-Gang electrical box).
- 3/4" vandle resistant wheel handle angle stop with back-check.
- Sweat adapter kit.
- Vacuum breaker with elbow flush connection.
- Wall flange, spud nut and spud flange for 3/4" back spud.
- All rubber parts molded of chloramine resistant rubber.

Electrical Accessories

- ☐ 2318A - Battery powered operation / Battery pack
- ☐ 2320-3 - Plug-in Transformer 9V DC for 3 valve installation
- ☐ 2324-3 - Hardwire Transformer 9V DC for 3 valve installation

Variations

- ☐ GJ - Ground Joint threaded (adjustable union tailpiece)
- ☐ SC - SlipFit Connection (adjustable joint tailpiece)
- ☐ TS - TruStop 1" Angle Control Stop

