

## TruSense Plus Bedpan Diverter

### Description


In-wall sensor activated exposed, diaphragm operated flush valve with Delany Bedpan Diverter for 1-1/2" top spud toilets. (For a Right Hand Rough Installation Only)

### Flush Cycle

1.28 gpf / 4.8 Lpf High Efficiency

### Specification

- Regulating screw for "True-in-the-Field" water conservation.
- Mashaerator self-cleaning bypass diaphragm.
- 9 volts DC low voltage transformer or battery.
- Renewable main valve seat.
- True Mechanical Override Button.
- Infrared sensor with detector indicator light.
- Arming delay of ten (10 ) seconds prevents unintentional flushes.
- Six (6) second flush delay.
- One-Touch Flush electronic override push button.
- Latching solenoid valve (9 volt DC).
- Chrome plated die cast wall plates for sensor and flush valve with no visible fasteners (for 2-Gang electrical box).
- 1" vandle resistant capped screwdriver angle stop with back-check.
- SlipFit Connection (adjustable joint tailpiece)
- Sweat adapter kit.
- Delany Bedpan Diverter Spray Arm.
- Vacuum breaker w/ 26-1/2" rough-in & 1-1/2" Offset
- Wall flange, spud nut and spud flange for 1-1/2" top spud.
- All rubber parts molded of chloramine resistant rubber.



### Electrical Accessories

- 2318A - Battery powered operation / Battery pack
- 2320-3 - Plug-in Transformer 9V DC for 3 valve installation
- 2324-3 - Hardwire Transformer 9V DC for 3 valve installation

### Variations

- GJ - Ground Joint threaded (adjustable union tailpiece)
- LHR - for Left Handed Rough-in valves
- T6 - Wall flange with allen set screw
- T36 - Solid ring wall support for flush connection
- T46 - Split ring wall support for flush connection
- TS - TruStop ball valve designed Control Stop
- VPS - Vandal Proof Control Stop with key

Valve is in compliance with the applicable sections of ASSE 1037.

