

TruSense Plus Bedpan Diverter

Description

In-wall sensor activated exposed, diaphragm operated flush valve with Delany Bedpan Diverter for 1-1/2" top spud toilets. (For a Right Hand Rough Installation Only)

Flush Cycle

1.6gpf / 6.0Lpf Low Consumption

Specification

- Regulating screw for "True-in-the-Field" water conservation.
- Masherator self-cleaning bypass diaphragm.
- 9 volts DC low voltage transformer or battery.
- Renewable main valve seat.
- True Mechanical Override Button.
- Infrared sensor with detector indicator light.
- Arming delay of ten (10) seconds prevents unintentional flushes.
- Six (6) second flush delay.
- One-Touch Flush electronic override push button.
- Latching solenoid valve (9 volt DC).
- Chrome plated die cast wall plates for sensor and flush valve with no visible fasteners (for 2-Gang electrical box).
- 1" vandle resistant capped screwdriver angle stop with back-check.
- SlipFit Connection (adjustable joint tailpiece)
- Sweat adapter kit.
- Delany Bedpan Diverter Spray Arm.
- Vacuum breaker w/ 26-1/2" rough-in & 1-1/2" Offset
- Wall flange, spud nut and spud flange for 1-1/2" top spud.
- All rubber parts molded of chloramine resistant rubber.

Electrical Accessories

- ☐ 2318A - Battery powered operation / Battery pack
- ☐ 2320-3 - Plug-in Transformer 9V DC for 3 valve installation
- ☐ 2324-3 - Hardwire Transformer 9V DC for 3 valve installation

Variations

- ☐ GJ - Ground Joint threaded (adjustable union tailpiece)
- ☐ LHR - for Left Handed Rough-in valves
- ☐ T6 - Wall flange with allen set screw
- ☐ T36 - Solid ring wall support for flush connection
- ☐ T46 - Split ring wall support for flush connection
- ☐ TS - TruStop ball valve designed Control Stop
- ☐ VPS - Vandal Proof Control Stop with key

Valve is in compliance with the applicable sections of ASSE 1037.



P.O. Box 411 • Charlottesville • VA • 22902 • USA Phone: (434) 296-0166 • Fax (434) 977-3596
Email: info@delanyproducts.com Web: www.delanyproducts.com ©2016 v1



True
Mechanical
Override

