

# E402-1.28-SM

HIGH EFFICIENCY TOILET FLUSH VALVE  
(1.28 gpf / 4.8 Lpf per Flush)

## EMPIRE

### Description

Exposed chrome plated, piston operated, flush valve for 1-1/2" top spud fixtures with side mounted sensor actuator.

### Flush Cycle

1.28gpf / 4.8Lpf High Efficiency

### Specification

- SideArm (Side Mounted Sensor Actuator)
  - Infrared Sensor with user indicator light
  - 6 volts DC low voltage four "C" batteries
  - 8 second arming delay to prevent unintentional flushes
- Nickel plated solid brass piston cartridge.
- Mashaerator self-cleaning bypass.
- ADA compliant metal "Rubberflex" oscillating handle.
- 1" vandle resistant capped screwdriver angle stop with back-check.
- Sweat adapter kit.
- Slip-Joint adjustable tailpiece.
- 1-1/2" x 9" vacuum breaker flush connection.
- Wall flange, spud nut and spud flange for 1.5" top spud.
- All rubber parts molded of chloramine resistant rubber

### Variations

- AM - Antimicrobial Coated Handle
- G - Bumper on angle stop (for seat without cover)
- SM - SideArm (Side Mounted Sensor Actuator)
- T6 - Wall flange with allen set screw
- T36 - Solid ring wall support for flush connection
- T46 - Split ring wall support for flush connection
- TS - TruStop - Ball valved designed Control Stop
- VPS - Vandal Proof Control Stop with Key

