

G1451-0.125

HIGH EFFICIENCY URINAL FLUSH VALVE
(0.125 gpf / 0.5 Lpf per Flush)

Description

Battery powered, sensor activated, diaphragm operated, chrome plated exposed flush valve for 0.75" top spud urinals.

Flush Cycle

0.125 gpf/0.5 Lpf High Efficiency

Specification

- SmartChoice Technology software provides field adjustability for True-in-the-Field Water Conservation
- Field adjustable range.
- Remote for Range & Discharge Adjustability.
- Chloramine resistant diaphragm.
- 6 Volt DC latching solenoid valve.
- 6 Volt DC lithium battery (2C-P2 type).
- Infrared sensor with Dual Infrared Transmitter Technology
- Arming delay of 10 seconds prevents unintentional flushes
- Electronic courtesy flush push button.
- 3/4" vandle resistant capped screwdriver angle stop with back-check.
- Renewable main valve seat.
- Sweat Adapter Kit.
- Vacuum Breaker w/ 9" flush connection.
- Wall flange, spud nut and spud flange for 3/4" top spud.
- All rubber parts molded of chloramine resistant rubber.

Variations

- GJ - Ground Jount Tailpiece
- SC - SlipFit Connection (adjustable joint tailpiece)
- T36 - Solid ring wall support for flush connection
- T46 - Split ring wall support for flush connection
- TS - TruStop - Ball valve designed Control Stop
- VPS - Vandal Proof Control Stop with Key

