


# GP3003A-1.6

LOW CONSUMPTION TOILET RETRO-FIT KIT  
(1.6 gpf / 4.8 Lpf per flush)

## TruEDGE Retro-Fit Kit



### Description

Battery powered, sensor activated, retro-fit kit for all Delany Flushboy and Flushboy ULTRA flush valves.

### Flush Cycle

1.6 gpf / 4.8 Lpf Low Consumption

### Specification

- SmartChoice Technology software provides field adjustability for True-in-the-Field Water Conservation
- Remote for Range & Discharge Adjustability.
- Mashaerator self-cleaning diaphragm.
- Chloramine resistant diaphragm.
- 6 Volt DC latching solenoid valve
- 6 Volt DC lithium battery (2C-P2 type).
- Infrared sensor with Dual Infrared Transmitter Technology.
- Arming delay of 10 seconds prevents unintentional flushes.
- Electronic courtesy flush push button.
- IP64 Standard connections and circuitry.
- Stress resistant connectors.
- Chloramine Resistant Solenoid



P.O. Box 411 • Charlottesville • VA • 22902 • USA Phone: (434) 296-0166 • Fax (434) 977-3596  
Email: [info@delanyproducts.com](mailto:info@delanyproducts.com) Web: [www.delanyproducts.com](http://www.delanyproducts.com) ©2016 v1